

PRODUCT PROFILE

ELECTRONIC PRESSURE SYSTEM BIA-INOX45S2MPCX - 804913

The pump is a self-priming surface mounted pressure system pump supplied with plug and play leads (IEC type). The self-priming ability provides excellent





suction capacity of up to 9m. Used especially for supplying water to domestic installations.

The pump is characterised by:

- Automatic electronic pump control fitted and wired with plug and play leads so a licensed electrician is not required during installation.
- Includes fully electronic pump controller for automatic pump starting, stopping and restart after power loss and water loss.
- Run dry protection to prevent pump damage
- Automatic electronic control has in-built check valve to prevent water backflow through the pump.
- 2.2bar pump cut in for greater versatility.
- Corrosion resistant pump body, diffuser and impeller to ensure pump durability
- High quality mechanical shaft seal and high quality bearings
- 240V single phase TEFC motor with in-built auto reset thermal overload to prevent the pump from overheating.

Applications

Used especially for supplying water to domestic installations and applications where a suction lift is required.

Package Information

- L 420mm x W 230mm x H 460mm

Liquid:

Liquid Type: Clean Water Clean water temperature range: 2 - 40oC

Materials:

Pump body, Impeller: Stainless Steel 304 Jet/Venturi, Diffuser: Noryl Glass Reinforced Mechanical seal: Carbon/Ceramic/Nitrile O rings: Nitrile

Power Cable: 2m Cable H05 3G1.0

Installation:

Maximum ambient temperature: 40oC Maximum operating pressure: 6 bar Pipe connections suction/discharge: 1"BSPF / 1"BSPM Dimensions: 420mm L x 460mm H x 230mm W

Electrical data:

Rated voltage: 220 (-6%) -240V (+6%) Mains frequency: 50 Hz

P2 (kW): 0.45 (Shaft Power) Current: 3.5 amps

Capacitor: 10 uF

Motor duty: Continuous


Motor type: Asynchronous, TEFC Motor protection: In-built thermal overload

Ingress protection: IP X4

Insulation class: F Net weight: 11 kg

Hydraulic Data:

Max Head: 38m Max Flow: 50 I/min Number taps: 4





DN2	<u> </u>
ž O	
1	
L	M8- W,

DN1	DN2	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
1"	1"	376	200	214	88.5	140	107

H (mm)	I (mm)	J (mm)	K (mm)	L (mm)	M (mm)
64	81	177	70	62	116



