




**STANDARD FITOUT**



**Standard Fit out Details:**

<b>Inlet</b>	@ 12 o'clock - 400mm inlet strainer
<b>Overflow</b>	@ 6 o'clock - 90mm overflow
<b>Outlet</b>	@ 12 o'clock - 25mm brass outlet with 38mm brass gate valve

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- Made in any standard COLORBOND® roofing colours

**Other fit out options:**

- Inlet is always at 12 o'clock
- The overflow and outlet can be placed at any position on the tank

**Dimensions:**

<b>Width/Diameter</b>	2380mm
<b>Inlet Height</b>	2410mm
<b>Total Height</b>	2485mm
<b>Weight (approx.)</b>	175kg

**Tank is Supplied with:**

1 x 400mm inlet strainer
1 x 90mm Overflow
1 x 90mm Overflow Cap
1 x 25mm Brass outlet
1 x 25mm Brass Gate Valve

*\*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate*

All Tankworld tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.