



Standard Fit out Details:

Inlet	@ centre of tank - 300mm inlet strainer
Overflow	@ 2 o'clock - 90mm overflow
Outlet	@ 8 o'clock - 25mm spinweld, hex nipple, 25mm brass gate valve

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- Made in any standard COLORBOND® roofing colours

Other fit out options

- Inlet is always at 12 o'clock
- Please note outlets and overflows can only be positioned at 10 to 2 and, 4 to 8 o'clock
- No fittings placed at 3 or 9 o'clock due to the curvature of tank

Dimensions:	
Length	1220mm
Width/Diameter	620mm
Inlet Height	2010mm
Total Height	2010mm
Weight (approx.)	65kg

Tank is Supplied with:
1 x 300mm inlet strainer
1 x 90mm Overflow
1 x 90mm Overflow Cap
1 x 25mm Flush Spinweld
1 x 25mm Hex Nipple
1 x 25mm Brass Gate Valve

**Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate*

All Tankworld tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.