



**Standard Fit out Details:**

<b>Inlet</b>	@ centre of tank - 300mm inlet strainer (no other location)
<b>Overflow</b>	@ 6 o'clock - 90mm overflow (moulded into tank)
<b>Outlet</b>	@ 12 o'clock - 25mm spinweld, hex nipple, with 25mm brass gate valve

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- No centre pole
- Made in any standard COLORBOND® roofing colours

**Other fit out options**

- Inlet is always in the centre and overflow at 6 o'clock
- The outlet can be placed at any position on the tank

**Dimensions:**

<b>Width/Diameter</b>	<b>1200mm</b>
<b>Inlet Height</b>	<b>2000mm</b>
<b>Total Height</b>	<b>2000mm</b>
<b>Weight (approx.)</b>	<b>60kg</b>

**Tank is Supplied with:**

<b>1 x 300mm inlet strainer</b>
<b>1 x 90mm Overflow Cap</b>
<b>1 x 25mm (1") Flush Spinweld</b>
<b>1 x 25mm (1") Hex Nipple BSP</b>
<b>1 x 25mm (1") Brass Gate Valve</b>

*\*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate*

All Tankworld tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.