




STANDARD FITOUT



**Standard Fit out Details:**

<b>Inlet</b>	<b>Centre - 300mm inlet strainer (no other location)</b>
<b>Overflow</b>	<b>@ 6 o'clock - 90mm overflow (moulded into tank)</b>
<b>Outlet</b>	<b>@ 12 o'clock - 25mm spinweld, hex nipple, with 25mm brass gate valve</b>

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- Made in any standard COLORBOND® roofing colours

**Other fit out options**

- Inlet is always in the centre and overflow at 6 o'clock

Dimensions:	
<b>Width/Diameter</b>	<b>1520mm</b>
<b>Inlet Height</b>	<b>2000mm</b>
<b>Total Height</b>	<b>2000mm</b>
<b>Weight (approx.)</b>	<b>85kg</b>

Tank is Supplied with:
<b>1 x 300mm inlet strainer</b>
<b>1 x 90mm Overflow Cap</b>
<b>1 x 25mm (1") Flush Spinweld</b>
<b>1 x 25mm (1") Hex Nipple BSP</b>
<b>1 x 25mm (1") Brass Gate Valve</b>

*\*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate*

All Tankworld tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.