



**Standard Fit out Details:**

<b>Inlet</b>	@ centre of tank - 300mm inlet strainer
<b>Overflow</b>	@ 10 o'clock - 90mm overflow
<b>Outlet</b>	@ 8 o'clock – 25mm spinweld, 25mm brass gate valve (base of tank)

- When no fit out is nominated standard fit out will be supplied
- Bucket tap not included with tank
- Made in any standard COLORBOND® roofing colours

**Other fit out options**

- Inlet is always in the centre of tank

Dimensions:	
<b>Length</b>	1220mm
<b>Width/Diameter</b>	620mm
<b>Inlet Height</b>	1220mm
<b>Total Height</b>	1260mm
<b>Weight (approx.)</b>	35kg

Tank is Supplied with:
1 x 300mm inlet strainer
1 x 90mm Overflow
1 x 90mm Overflow cap
1 x 25mm Flush Spinweld
1 x 25mm Hex Nipple
1 x 25mm Brass Gate Valve

**NO OTHER FIT OUT OPTIONS**

*\*Dimensions of our tanks can vary slightly due to shrinkage variations. All dimensions are approximate*

All Tankworld tanks are manufactured in Australia to the Australian Polyethylene tank standard using UV stabilised Polyethylene complying with AS/NZS 4020 and AS/NZS 2070.